



CommClean™ Oil Rejecting Metal Cleaner



WHAT IT DOES:

In many regions, separation of oil and grease from industrial effluent is the most pressing issue facing companies who wish to discharge industrial waste water as part of their operation. Once only the problem of large facilities, the Federal Government and/or local municipalities have targeted any operation performing industrial cleaning. It has long been a problem to design products that clean, emulsify and then release oily soils for separation and then allowing "clean" water to be discharged. After extensive research, Commonwealth Oil is pleased to announce **CommClean™ Oil Rejecting Metal Cleaner**, a state of the art formulation designed to solve the above problems and more. **CommClean™ Oil Rejecting Metal Cleaner** rinses away quickly and easily to leave no residue. It is very important to have cleaned rinsed parts that are ready for additional processing. **CommClean™ Oil Rejecting Metal Cleaner** is the product of choice for use in Industrial Spray Washers such as Bowden, Proceco, Mart and Ransolhoff etc. **CommClean™ Oil Rejecting Metal Cleaner** performs exceptionally well in these types of washers where you depend on quality and clean parts.

WHERE TO USE IT:

CommClean™ Oil Rejecting Metal Cleaner may be used at 2 - 10% dilution depending on soil being cleaned and the temperature of the fluid. Additions of **CommClean™ Oil Rejecting Metal Cleaner** liquid can be made to extend bath life of the cleaning solution.

PERFORMANCE BENEFITS:

CommClean™ Oil Rejecting Metal Cleaner is especially formulated to deliver the following performance benefits:

- Separates Oil
- Biodegradable
- Non-flammable



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com

CommClean™ Oil Rejecting Metal Cleaner



TECHNICALLY SPEAKING:

Test	CommClean™ Oil Rejecting Metal Cleaner
Color:	Clear, Yellow Liquid
Odor:	Detergent Odor
Flash Point, COC °C/°F	None
pH	13
Foam	Low
Density, lbs./US Gallon	9.8
Specific Gravity	1.18

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.

1. Wear splash goggles and rubber gloves when handling an industrial grade cleaner.
2. Indoor storage, above freezing preferred.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com