



## Commform™ Aqua Plus All Season Water Based Concrete Form Release

### WHAT IT DOES:

Commonwealth Oil's **Commform™ Aqua Plus All Season** is a water based chemically active concrete form release fluid with a low freezing point. **Commform™ Aqua Plus All Season** virtually eliminates bugholes, is non-staining and offers easy release. **Commform™ Aqua Plus All Season** is easy to apply and non-hazardous.

### WHERE TO USE IT:

**Commform™ Aqua Plus All Season** can be applied to steel, plastic, fiberglass and overlaid plywood forms in precast applications.

**Commform™ Aqua Plus All Season** is applied by high and low pressure sprayers as well as other methods.

**Directions for Use:** Form surfaces should be clean and free from contaminants to ensure optimum performance of the release agent. For best appearance on formed concrete surfaces, apply a thin coating by using a roller, brush or sprayer. Wipe off any excess accumulation of release, as this condition may inhibit performance of release. Sprayer pressure should be no more than 60 PSI and proper spray tip should produce an oval pattern during application.

### PERFORMANCE BENEFITS:

**Commform™ Aqua Plus All Season** offers the following benefits:

- Non-hazardous
- Eliminates bugholes
- Non-staining
- Produces excellent surface finishes
- Low fogging and misting
- Low freezing point - suitable for year round use
- Suitable for various precast and drycast concrete mixtures



**Precautions:** At below freezing temperatures, release agent will thicken and reasonable care should be taken to maintain release thickness to ensure optimum performance.

**Typical Coverage Rates:** Rates may vary upon application or upon the medium used for forming.

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 [inquiries@commonwealthoil.com](mailto:inquiries@commonwealthoil.com) • [www.commonwealthoil.com](http://www.commonwealthoil.com)



## TECHNICALLY SPEAKING:

Test	Commform™ Aqua Plus All Season
Colour	Clear, Golden Yellow
pH	9.7
Freezing Point	-47°C / -52.6°F
Viscosity (cSt @ 23°C)	27
VOC content (theoretical) g/L	<250
Density, lbs./US Gallon	9.10
Specific Gravity	1.09

These are typical figures and do not constitute a specification.

### Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



### Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com