



Commonwealth Oil

Commform™ Gold Concrete Form Release Oil



WHAT IT DOES:

Commonwealth Oil's **Commform™ Gold** is a petroleum based chemically active concrete form release fluid which has been specially formulated with a lubricity additive. **Commform™ Gold** minimizes bugholes, is non-staining and offers easy release. **Commform™ Gold** is easy to apply, non-hazardous and is compliant with reduced VOC limits legislation in Canada and the United States.

WHERE TO USE IT:

Commform™ Gold can be applied to steel, plastic, fiberglass and overlaid plywood forms in precast applications.

Commform™ Gold is applied by high and low pressure sprayers as well as other methods.

Directions for Use: Form surfaces should be clean and free from contaminants to ensure optimum performance of the release agent. For best appearance on formed concrete surfaces, apply a thin coating by using a roller, brush or sprayer. Wipe off any excess accumulation of release, as this condition may inhibit performance of release. Sprayer pressure should be no more than 60 PSI and proper spray tip should produce an oval pattern during application.

PERFORMANCE BENEFITS:

Commform™ Gold offers the following benefits:

- Non-hazardous
- Minimizes bugholes
- Non-staining
- Produces excellent surface finishes
- Low fogging and misting
- Low pour point - suitable for year round use
- Suitable for various precast and drycast concrete mixtures
- Low VOC content



Precautions: At below freezing temperatures, release agent will thicken and reasonable care should be taken to maintain release thickness to ensure optimum performance.

Typical Coverage Rates: Rates may vary upon application or upon the medium used for forming.

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



TECHNICALLY SPEAKING:

| Test | Commform™ Gold |
|---------------------------------|----------------------|
| Viscosity: cSt @ 40°C | 10 |
| Colour | Clear, Golden Yellow |
| Flash Point, COC °C | > 140 |
| Flash Point, COC °F | > 284 |
| VOC content (ASTM E1868-10) g/L | 60.5 |
| Density, lbs./US Gallon | 7.01 |
| Specific Gravity | 0.840 |

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers