



# Commonwealth Oil

## Commvan™ 110 Vanishing Oil



### WHAT IT DOES:

Commonwealth Oil's **Commvan™ 110** is a low viscosity fluid primarily intended for light stamping and drawing of sheet metals. **Commvan™ 110** evaporates completely, leaving virtually no residues and no stains. **Commvan™ 110** is a very good choice for the manufacture of wires and stamp parts that require some painting or coatings, without first being cleaned.

### WHERE TO USE IT:

**Commvan™ 110** is ideal for applications such as:

- Light stamping and drawing of sheet metals
- Manufacture of wires and stamp parts that require painting or coating, without first being cleaned

### PERFORMANCE BENEFITS:

**Commvan™ 110** is especially formulated to deliver the following benefits and safety features.

#### Benefits:

- Non-corrosive and non-staining towards copper and aluminum
- Excellent EP/Anti-Wear Properties
- Provides good surface finishes
- Excellent rust inhibition

#### Safety Features:

- High flash solvent cleaner
- Odorless per FDA Regulation 21CFR 172.884
- High TLV (higher than varsol)
- Quickly penetrates greasy oil contaminates
- Can be used on all metals and painted surfaces
- Manufactured using FDA Approved raw materials suitable for direct and indirect food related applications per FDA Regulation 21CFR 172.882 and 21CFR 178.3530



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



## TECHNICALLY SPEAKING:

Test	Commvan™ 110
Viscosity: cSt @ 40°C	1.64
Colour: ASTM	< 0.5
Residual Odor	Nil
Sulphur, ppm	< 1
Volatiles: %	100
Flash Point, COC °C	63 minimum
Flash Point, COC °F	147.2 minimum
Dry Point °C (°F)	204 (400)
Distillation: IBP °C (°F)	179 (355)
Density, lbs./US Gallon	6.59
Specific Gravity	0.79

These are typical figures and do not constitute a specification.

### Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



**Available in Pails, Drums and One-Way Bulk Containers**

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 [inquiries@commonwealthoil.com](mailto:inquiries@commonwealthoil.com) • [www.commonwealthoil.com](http://www.commonwealthoil.com)