



## Supreme™ High VI 46 Hydraulic Fluid



### WHAT IT DOES:

Commonwealth Oil's **Supreme™ High VI 46 Hydraulic Fluid** is premium quality lubricant that meets the arduous demands of most off highway plant and stationary hydraulic systems exposed to wide temperature fluctuations. **Supreme™ High VI 46 Hydraulic Fluid** offers excellent anti-wear performance and oxidation stability. **Supreme™ High VI 46 Hydraulic Fluid** offers excellent protection against rust, corrosion, foam and metal fatigue. **Supreme™ High VI 46 Hydraulic Fluid** is specially formulated for operation under wide temperature ranges using synthetic base stocks.

### WHERE TO USE IT:

**Supreme™ High VI 46 Hydraulic Fluid** is suitable for use in off highway equipment and other hydraulic systems exposed to wide temperature fluctuations.

### PERFORMANCE BENEFITS:

**Supreme™ High VI 46 Hydraulic Fluid meets or exceeds the requirements for industrial and mobile hydraulic systems which call for:**

- Vickers I-286-S, M-2950-S
- Racine, variable volume vane pumps
- DIN 51524, Part 2
- Jeffrey No. 87
- U.S. Steel 136, 127
- General Motors LH-04-1, LH-06-1, LH-15-1
- Denison HF-1, HF-2, HF-0
- Cincinnati Milacron P-68, P-69, P-70
- Lee-Norse 100-1
- Ford M-6C32
- B. F. Goodrich 0152
- AFNOR E 48-603



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com

# Supreme™ High VI 46 Hydraulic Fluid

## TECHNICALLY SPEAKING:

Test	Supreme™ High VI 46 Hydraulic Fluid
Viscosity: cSt @ 40°C	48.0
Viscosity: cSt @ 100°C	8.70
Viscosity: SUS @ 100°F	97
Viscosity: SUS @ 210°F	25
Flash Point, COC °C/°F	>200/392
Pour Point, °C/°F	-24/-12
Viscosity Index	160
Rust, Distilled Water	Pass
Density, lbs/US Gallon	7.07
Specific Gravity	0.850

These are typical figures and do not constitute a specification.

### Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



**Available in 19L/5US Gal Pails, 208L/55US Gal Drums**

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 [inquiries@commonwealthoil.com](mailto:inquiries@commonwealthoil.com) • [www.commonwealthoil.com](http://www.commonwealthoil.com)