



Synercut SC 20 Active Sulfurized/Chlorinated Cutting Oil



WHAT IT DOES:

Synercut™ SC 20 is an active sulfurized, chlorinated, high performance cutting oil for ferrous metals.

WHERE TO USE IT:

Synercut™ SC 20 can be used in the following applications:

- Gundrill Operations
- Milling
- Screw Machines
- Reaming
- Turning
- Boring
- Thread Rolling
- Broaching
- Tapping
- Threading

PERFORMANCE BENEFITS:

Synercut™ SC 20 is especially formulated to deliver the following results:

- Active sulfurized, chlorinated cutting oil
- Provide superior lubrication for high stock removal in demanding operations
- Great for ferrous metals
- Low viscosity will help to quickly flush chips
- Low mist to help protect the operators
- Light coloured for excellent workpiece and tool visibility



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



TECHNICALLY SPEAKING:

Test	Synercut™ SC 20
Viscosity: cSt @ 40°C	22
Flash Point, COC °C	> 160
Flash Point, COC °F	> 320
% Sulfur (active)	2.1
% Chlorine	2.3
Copper Corrosion	4C
Density, lbs./US Gallon	7.34
Specific Gravity	0.88

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0
519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com