



Commonwealth Oil

Synercut™ SS Heavy Duty Cutting Oil



WHAT IT DOES:

Synercut™ SS is a heavy duty amber colored cutting oil. It contains sulphur, chlorine, wetting and anti-weld agents, along with premium base oils. **Synercut™ SS** has been specially formulated with a low volatility fatty additive that has proven itself far superior to previous fatty oil technology. This combination of additives provides excellent extreme pressure properties when pipe threading, tapping, reaming or broaching.

WHERE TO USE IT:

Synercut™ SS is designed for the most demanding metal removal applications. It is particularly well suited to the machining of stainless steels. It can be used on copper and it's alloys and as a dual purpose oil.

PERFORMANCE BENEFITS:

Synercut™ SS has been specifically formulated to deliver the following performance benefits:

- Low mist
- Effective defoamer package
- Contains no active sulphur



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



TECHNICALLY SPEAKING:

Property	Synercut™ SS
Appearance	Transparent amber coloured solution
Odour	Slight hydrocarbon odor
Flash Point (°C/°F)	199/390
Viscosity, cSt @ 40°C	40.0
Density, lbs./US Gallon	8.17
Specific Gravity	0.98

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com