



Regal Complex™ EP #2 Grease



WHAT IT DOES:

Regal Complex™ EP #2 grease is a versatile, long lasting, lithium complex based multi-purpose grease meeting the lubrication requirements of plain and anti-friction bearings, gears, and couplings in general industrial applications. This product maintains outstanding lubricity throughout a wide variety of operating conditions and temperatures. **Regal Complex™ EP** greases contain no lead or other heavy metals.

WHERE TO USE IT:

Regal Complex™ EP #2 is effectively used in:

- Plain and anti-friction bearings
- Gears and couplings

If continuous excessive high temperature conditions are anticipated, call Commonwealth Oil for information on our Regal Ultra-Life™, a poly-urea based grease specifically engineered for high temperature operations.

PERFORMANCE BENEFITS:

Regal Complex™ EP greases provide the following benefits:

- Water washout resistance
- High temperature performance
- Resistance to mechanical breakdown or shearing
- Good rust protection
- Fortified with extreme pressure properties
- Excellent oxidation resistance





TECHNICALLY SPEAKING:

Test	ASTM Method	Regal Complex™ EP #2
Penetration 60 Strokes @ 77°F	D-217	265 - 295
Dropping Point	D-2265	250°C (482°F)
Timken OK Load, Lbs.	D-2509	45
Oxidation Stability 100 Hrs@210°F PSI loss	D-942	4
Rust Prevention Rating	D-1743	Pass
Base Oil:		
Viscosity @ 210°F., SUS	D-2161	75.6
Viscosity @ 100°F., SUS	D-2161	774
Viscosity @ 100°C., cSt.	D-445	13.98
Viscosity @ 40°C., cSt.	D-445	147
Viscosity Index	D-2270	90
Four Ball Weld, kg	D-2596	250
Water Washout @ 175°F, % Loss	D-1264	10
Pour Point	8	-13°C (10°F)
Wheel Bearing Leakage, grams	D-1263	2

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com