



AirSpin™ 3, 9 and 22

Pneumatic Tool & Spindle Lubricant



WHAT IT DOES:

AirSpin™ lubricants are the finest quality lubricants for high-speed fractional horsepower motors, pneumatic tools and some hydraulic mechanisms. They are inhibited against rust and wear to provide the maximum protection, thus preventing premature breakdowns.

WHERE TO USE IT:

- High-speed fractional horsepower motors
- Pneumatic tools
- Hydraulic mechanisms
- Textile industry
- Automatic machine tools

PERFORMANCE BENEFITS:

- Excellent corrosion inhibition.
- Protection against premature breakdown.
- Outstanding anti-wear properties
- Exceptional protection from rust and oxidation with superior oxidation stability
- Water separation characteristics
- Non-corrosiveness to metals



AirSpin™ 3, 9 AND 22

Pneumatic Tool & Spindle Lubricant



TECHNICALLY SPEAKING:

Test	AirSpin™ 3	AirSpin™ 9	AirSpin™ 22
Viscosity: cSt @ 40°C	3.5 to 5.5	9	22
Viscosity: cSt @ 100°C	< 3.0	2.5	4.3
Viscosity: SUS @ 100°F	< 60	55.4	106.3
Viscosity: SUS @ 210°F	< 32	34.5	40.4
Viscosity Index	100	94	98.5
Flash Point, COC °C	> 120	> 125	> 165
Flash Point, COC °F	> 248	> 257	> 329
Pour Point °C	-33	-39	-30
Pour Point °F	-27	-38	-22
Rust, Distilled Water	Pass	Pass	Pass
Density, lbs./US Gallon	7.03	6.91	7.07
Specific Gravity	0.845	0.831	0.850

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in 19L/5US Gal Pails, 208L/55US Gal Drums and 1250L/330US Gal Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com