

CommGuard™ 200 Synthetic Rust Inhibitor



WHAT IT DOES:

CommGuard™ 200 Rust Inhibitor is a water based, synthetic film rust inhibitor for protection of both ferrous and non-ferrous metals. **CommGuard™ 200 Rust Inhibitor** is ideal for the protection of tubing and bar stock, as well as precision parts. This product has been specially formulated to offer improved rust protection over and above other synthetic rust inhibitors.

WHERE TO USE IT:

CommGuard™ 200 is compounded for use in tough environments and is most effective when used under the following conditions:

PROPER MIXING AND CARE OF COOLANTS

- Always add concentrate to water with a small amount of agitation
- Protect product from freezing
- If product has frozen, allow it to thaw naturally and completely to room temperature. The product should be checked for consistency. If necessary, product can be re-mixed with slight agitation
- Store coolant containers indoors. If coolant drums must be stored outdoors, place them on their sides to minimize the potential for water to enter drums
- Never expose coolants to temperature extremes
- Do not add anything to this product unless recommended by Commonwealth Oil
- **CommGuard™ 200** can be diluted from 10% to 15% with most tap water for 60 – 90 days indoor rust protection.

PERFORMANCE BENEFITS:

CommGuard™ 200 Rust Preventative has been specifically formulated to provide the following benefits:

- Improved rust protection of both ferrous and non-ferrous metals.
- User friendly.
- No flash point. Non-combustible.
- Nitrite, chrome and phenol free.
- Non-foaming
- Exceptional indoor rust protection for tube, pipe and bar stock.
- Not messy. Cleaner environment as compared to oil base rust inhibitors.



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



TECHNICALLY SPEAKING:

Test	CommGuard™ 200
pH Concentrated	10.10
pH 5% Solution	9.6
Refractive Index (RI) Factor	Multiply RI by 3.45 for Concentration %
RI for a 5% Solution	1.45
RI for a 10% Solution	2.90
RI for a 15% Solution	4.35
Flash Point, COC	None
Density, lbs./US Gallon	8.678
Specific Gravity	1.04

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0
519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com