

Commform VO 15

Readily Biodegradable Concrete Form Release Agent



WHAT IT DOES:

Commonwealth Oil's **Commform VO 15** is a readily biodegradable, chemically active concrete form release fluid which has been specially formulated with a lubricity additive for easy release. **Commform VO 15** is suitable for use on vertical forming applications and resists running and pooling. **Commform VO 15** minimizes bug holes, is non-staining and offers easy release. **Commform VO 15** is easy to apply and non-hazardous.

WHERE TO USE IT:

Commform VO 15 can be applied to steel, plastic, fiberglass and overlaid plywood forms in precast applications.

Commform VO 15 is applied by high and low pressure sprayers as well as other methods.

Directions for Use: Form surfaces should be clean and free from contaminants to ensure optimum performance of the release agent. For best appearance on formed concrete surfaces, apply a thin coating by using a roller, brush or sprayer. Wipe off any excess accumulation of release, as this condition may inhibit performance of release. Sprayer pressure should be no more than 60 PSI and proper spray tip should produce an oval pattern during application.

PERFORMANCE BENEFITS:

Commform VO 15 offers the following benefits:

- Non-hazardous
- Readily Biodegradable
- Low VOC Content (below 250 g/L)
- Minimizes bugholes
- Non-staining
- Produces excellent surface finishes
- Low fogging and misting
- Lowered pour point
- Suitable for various precast and drycast concrete mixtures



Precautions: At below freezing temperatures, release agent will thicken and reasonable care should be taken to maintain release thickness to ensure optimum performance.

Typical Coverage Rates: Rates may vary upon application or upon the medium used for forming.

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



TECHNICALLY SPEAKING:

Test	Commform VO 15
Viscosity: cSt @ 40°C	15.0
Colour	Clear, Golden Yellow
Flash Point, COC °C	> 120
Flash Point, COC °F	> 248
Pour Point °C/°F	-12 / 10.4
Density, lbs./US Gallon	7.18
Specific Gravity	0.860
VOC Content (g/L)	111.4
Biodegradability – ASTM D5864	Readily Biodegradable

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com