

Hocut WS 300 CA (Formerly AquaComm)



WHAT IT DOES:

Commonwealth Oil's **Hocut WS 300 CA** is a general-purpose soluble oil, (water emulsifiable) cutting oil serving a variety of functions. **Hocut WS 300 CA** does not stain aluminum and has excellent corrosion resistance. **Hocut WS 300 CA** is typically used at a 20:1 dilution and does not contain active sulphur or chlorine extreme pressure agents.

WHERE TO USE IT:

Hocut WS 300 CA is effectively used in:

- Screw Machines
- Drilling
- Boring
- Milling
- Broaching
- Tapping
- Threading/Turning

PERFORMANCE BENEFITS:

Hocut WS 300 CA is especially formulated to provide the following benefits:

- Non-staining
- Good corrosion resistance
- General-purpose soluble oil typically used at a 20:1 dilution
- Does not contain active sulphur or chlorine extreme pressure agents
- Very reliable and economical.



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com

Hocut WS 300 CA



TECHNICALLY SPEAKING:

Test	Hocut WS 300 CA
Specific Gravity @ 20°C (68°F)	0.90
Lbs./U.S. Gallon	7.51
pH @ 5% Emulsion	9.2
% Phosphorus	Nil
% Chlorine	Nil
Refractive Index Multiplier	1.0
Refractive Index @ 5%	5.0
Refractive Index @ 10%	10.0

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0
519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com