

Proway Way Lubricants



WHAT IT DOES:

Commonwealth Oil's **Proway Way Lubricants** are designed to provide the trouble-free results on slide-ways that people have come to expect where accurate machining is required.

Proway Way Lubricants are available in three viscosity grades.

WHERE TO USE IT:

- Machine tool slides and tables.
- Chains, cables and other parts requiring tackified lubricants.
- Anywhere where a combination hydraulic oil and machine way lubricant are necessary.
- Combined hydraulic and tableway applications.
- **Proway 4 ISO 220T** may be used for larger, more heavily loaded machines.

PERFORMANCE BENEFITS:

Due to our unique formulas combining highly refined High Viscosity Index base oils with friction modifiers, we have virtually eliminated the term stick-slip from machining vocabulary. This provides the machinist with the following advantages:

- Rejects emulsification by alkaline coolants.
- **Proway Way Lubricants** make it easier to separate the tramp oil from your coolant tank, which helps extend the life of your coolant.
- Excellent metal wetting and anti-wear properties, imparts good rust prevention as well.
- **Proway Way Lubricants** have excellent thermal stability, EP properties and lubricity.
- Increases the accuracy of automatic machinery, as product will resist squeezing out.
- Excellent non-drip characteristics that reduce film rupture and decreases housekeeping problems.
- Low or no stick-slip reaction, for smoother way operation.
- **Proway Way Lubricants** have tackiness to improve its ability to stay in place.





TECHNICALLY SPEAKING:

Test	Proway 2 ISO 68T	Proway 3 ISO 150T	Proway 4 ISO 220T
Viscosity: cSt @ 40°C	68.0	150.0	220.0
Flash Point, COC °C	221	224	229
Flash Point, COC °F	430	435	445
Pour Point °C	-6	-9	-6
Pour Point °F	20	15	20
Density, lbs./US Gallon	7.22	7.4727	7.35
Specific Gravity	0.868	0.890	0.884

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com