

## **RUST VETO 113B** (Formerly Commguard 113B)



### **WHAT IT DOES:**

**RUST VETO 113B** is an outstanding water displacing, non-staining rust preventative that will rapidly separate water from metal surfaces after machining operations and/or alkali cleaning. **RUST VETO 113B** is concentrated and will provide extended protection.

### **WHERE TO USE IT:**

**RUST VETO 113B** can be used on any metal surface after machining operations and/or alkali cleaning.

**RUST VETO 113B** Rust Preventative can be applied by brushing, dipping or spraying. The ultra-thin film left behind will provide effective protection of ferrous and non-ferrous metals from atmospheric corrosion even under conditions of high humidity. The resultant film left behind, upon total evaporation of the carrier, should be faintly visible.

### **PERFORMANCE BENEFITS:**

**RUST VETO 113B** is especially formulated to deliver the following benefits:

- Concentrated to provide extended corrosion protection.
- Protection of ferrous and non-ferrous metals from atmospheric corrosion even under conditions of high humidity.
- **RUST VETO 113B** will easily pass the ASTM D-1748 Humidity Testing at more than 75 Hours.
- When the film is properly prepared the **RUST VETO 113B** pass a minimum of 3 hours neutral salt spray test as outlined in ASTM B-117.



# RUST VETO 113B



## TECHNICALLY SPEAKING:

| Test                                     | RUST VETO 113B |
|--|----------------|
| Viscosity: cSt @ 40°C                    | 1.7            |
| Viscosity: SUS @ 100°F                   | 8.0            |
| Flash Point, COC °C                      | > 64           |
| Flash Point, COC °F                      | > 148          |
| Specific Gravity                         | 0.800          |
| Density lbs/US gallon                    | 6.68           |
| Melting Pt., °F Residual Film            | 103            |
| Copper Corrosion, 3 Hrs., 100°C, (212°F) | 1A             |

These are typical figures and do not constitute a specification.

### Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



**Available in Pails, Drums and One-Way Bulk Containers**

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0  
519-738-3503 • 800-265-3689 • FAX- 519-738-3335 [inquiries@commonwealthoil.com](mailto:inquiries@commonwealthoil.com) • [www.commonwealthoil.com](http://www.commonwealthoil.com)