



## Vanishing Oil 108

### WHAT IT DOES:

Commonwealth Oil's **Vanishing Oil 108** is a low viscosity fluid primarily intended for light stamping and drawing of sheet metals. **Vanishing Oil 108** evaporates completely, leaving virtually no residues and no stains. **Vanishing Oil 108** is a very good choice for the manufacture of wires and stamp parts that require some painting or coatings, without first being cleaned.

### WHERE TO USE IT:

**Vanishing Oil 108** is ideal for applications such as:

- Light stamping and drawing of sheet metals
- Manufacture of wires and stamp parts that require painting or coating, without first being cleaned

### PERFORMANCE BENEFITS:

**Vanishing Oil 108** is especially formulated to deliver the following benefits and safety features.

#### Benefits:

- Non-corrosive and non-staining towards copper and aluminum
- Excellent EP/Anti-Wear Properties
- Provides good surface finishes
- Excellent rust inhibition

#### Safety Features:

- Light colour and very mild odor
- Contains no chlorinated paraffins or 1,1,1 Trichloroethane
- Low aromatic content
- No extra safety precautions are needed to perform normal working functions



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



## TECHNICALLY SPEAKING:

Test	Vanishing Oil 108
Viscosity: cSt @ 40°C	2.1
Colour: ASTM	1.0
Residual Odour	Nil
Sulphur, PPM	< 1
Volatiles: %	96
Flash Point, COC °C	> 65.5
Flash Point, COC °F	> 149.9
Dry Point °C (°F)	200 (392)
Distillation: IBP °C (°F)	157 (314)
Density, lbs./US Gallon	6.676
Specific Gravity	0.800

These are typical figures and do not constitute a specification.

### Handling & Safety Information

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



**Available in Pails, Drums and One-Way Bulk Containers**

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 [inquiries@commonwealthoil.com](mailto:inquiries@commonwealthoil.com) • [www.commonwealthoil.com](http://www.commonwealthoil.com)