

## Vanishing Oil 110



### WHAT IT DOES:

Commonwealth Oil's **Vanishing Oil 110** is a low viscosity fluid primarily intended for light stamping and drawing of sheet metals. **Vanishing Oil 110** evaporates completely, leaving virtually no residues and no stains. **Vanishing Oil 110** is a very good choice for the manufacture of wires and stamp parts that require some painting or coatings, without first being cleaned.

### WHERE TO USE IT:

**Vanishing Oil 110** is ideal for applications such as:

- Light stamping and drawing of sheet metals
- Manufacture of wires and stamp parts that require painting or coating, without first being cleaned

### PERFORMANCE BENEFITS:

**Vanishing Oil 110** is especially formulated to deliver the following benefits and safety features.

#### Benefits:

- Non-corrosive and non-staining towards copper and aluminum
- Excellent EP/Anti-Wear Properties
- Provides good surface finishes
- Excellent rust inhibition

#### Safety Features:

- High flash solvent cleaner
- Odorless per FDA Regulation 21CFR 172.884
- High TLV (higher than varsol)
- Quickly penetrates greasy oil contaminates
- Can be used on all metals and painted surfaces
- Manufactured using FDA Approved raw materials suitable for direct and indirect food related applications per FDA Regulation 21CFR 172.882 and 21CFR 178.3530





## TECHNICALLY SPEAKING:

Test	Vanishing Oil 110
Viscosity: cSt @ 40°C	1.64
Colour: ASTM	< 0.5
Residual Odor	Nil
Sulphur, ppm	< 1
Volatiles: %	100
Flash Point, COC °C	63 minimum
Flash Point, COC °F	147.2 minimum
Dry Point °C (°F)	204 (400)
Distillation: IBP °C (°F)	179 (355)
Density, lbs./US Gallon	6.59
Specific Gravity	0.79

These are typical figures and do not constitute a specification.

### Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



**Available in Pails, Drums and One-Way Bulk Containers**

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 [inquiries@commonwealthoil.com](mailto:inquiries@commonwealthoil.com) • [www.commonwealthoil.com](http://www.commonwealthoil.com)