

WOCO Hydraulic Tracer Fluid 32

WHAT IT DOES:

Commonwealth Oil's **WOCO Hydraulic Tracer Fluid 32** is premium quality lubricant made from highly refined base stock. **WOCO Hydraulic Tracer Fluid 32** is dyed red and can be used as a leak detection fluid in hydraulic systems. **WOCO Hydraulic Tracer Fluid 32** is specially formulated for operation under "normal" ambient temperature ranges and is compounded with an additive package to assure excellent protection against wear, foam, rust and oxidation. **WOCO Hydraulic Tracer Fluid 32** is compatible with most petroleum based hydraulic fluids.

WHERE TO USE IT:

WOCO Hydraulic Tracer Fluid 32 is suitable for use in most hydraulic applications requiring a low viscosity fluid. **WOCO Hydraulic Tracer Fluid 32** is dyed red for visibility when used a leak detection fluid.

For silver-plated hydraulic pump parts, use Commonwealth Oil's WOCO Turbine & Hydraulic Oil.

TECHNICALLY SPEAKING:

Test	WOCO Hydraulic Tracer Fluid 32
Viscosity: cSt @ 40°C	32.0
Viscosity: cSt @ 100°C	5.3
Viscosity: SUS @ 100°F	150.5
Viscosity: SUS @ 210°F	43.6
Flash Point, COC °C/°F	>205/401
Pour Point, °C/°F	-30/-22
Viscosity Index	98.3
Rust, Distilled Water	Pass
Density, lbs/US Gallon	7.16
Specific Gravity	0.860

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.

Available in 19L/5US Gal Pails, 208L/55US Gal Drums

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0
 519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com