

WOCO Supreme HTD



WHAT IT DOES:

WOCO Supreme HTD is a specially blended multi-purpose fluid most often used in farm and industrial tractors and equipment that utilizes a common sump. Because the common sump system uses a single fluid for many hydraulic systems - transmissions, differentials, wet clutches and brakes, for example - the demands on a fluid are strenuous. **WOCO Supreme HTD** from Commonwealth Oil is built rugged to handle these demands.

WHERE TO USE IT:

WOCO Supreme HTD is a multi-grade SAE 10W-20 fluid, suitable for year-round service where any of the following are normally acceptable:

- Agco including Massey Ferguson PF-821XL, M-1110, 1127A/B, 1129-A, 1135, 1141, 1143.
- John Deere - Type 303, Hygard J20A,B,C,D, Quatrol®, J14B/C, J21A
- J.I. Case - TCH & TDF Fluid, JIC-145 & 185, MS-1204, 1205, 1206, 1207, 1210. B-6, SEMS 17001 (Steiger)
- New Holland including Ford, Sperry-Vickers, Versatile, New Holland, Fiat, FNHA-2-C-201 (134-D Fluid), FNHA-2-C-200, ESN-M2C134-A/B/C/D, ESN-M2-C41-B, M2-C53-A/B, ESN-M2-C86-A,B,C, 23M or 24M (Versatile), I-286-S, M2950-S (Vickers)
- White Including Minneapolis-Moline, Oliver, & New Idea- UHFT, Type 55, Q-1705, 1722, 1766 (B) & 1826
- Kubota UDT
- Allison C-4
- Caterpillar TO-2
- Denison HF-0, HF-1, HF-2
- Belarus, Claas, Clark, David Brown (part of CASE), Eaton Hydraulics, IMT, International Hough (Dresser), JCB, Kioto, Komatsu & Komatsu/Dresser, Landini, Leyland, McCormick Farmall (part of CASE), Mitsubishi, Rockwell Transmissions, Same Deutz-Fahr, Sundstrand Hydraulics, Universal, Valmet, Vickers Hydraulics, Volvo and Yanmar

PERFORMANCE BENEFITS:

WOCO Supreme HTD is formulated from only the highest quality ingredients to provide the following benefits:

- Excellent protection against wear and oxidation
- Protect hydraulic systems under high pressure operation
- Protect transmissions and differentials under heavy loads
- Superior gear performance, chatters suppression, hydraulic pumps and low temperature performance.



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com



TECHNICALLY SPEAKING:

Test	Methods	WOCO Supreme HTD
Viscosity: cSt @ 40°C	D-445	57.5
Viscosity: cSt @ 100°C	D-445	8
Viscosity: SUS @ 100°F	D-2161	267
Viscosity: SUS @ 210°F	D-2161	50
Viscosity Index	D-2270	154
Flash Point, COC °C	D-92	180
Flash Point, COC °F	D-92	356
Pour Point °C	D-97	< -18
Pour Point °F	D-97	< -0.4
Density, lbs./US Gallon	D-1298	7.37
Specific Gravity	D-1298	0.883

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



Available in Pails, Drums and One-Way Bulk Containers

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com