

Wocospin 3, 10 and 22

Pneumatic Tool & Spindle Lubricant
(Formerly Airspin 3, 9 and 22)



WHAT IT DOES:

Wocospin spindle lubricants are the finest quality lubricants for high-speed fractional horsepower motors, pneumatic tools and some hydraulic mechanisms. They are inhibited against rust and wear to provide the maximum protection, thus preventing premature breakdowns.

Wocospin spindle oils may be used in hydraulic systems where light viscosity oils are required.

WHERE TO USE IT:

- High-speed fractional horsepower motors
- Pneumatic tools
- High speed spinning and twister spindle bearings
- Hydraulic mechanisms
- Textile industry
- Automatic machine tools

PERFORMANCE BENEFITS:

- Excellent corrosion inhibition.
- Protection against premature breakdown.
- Outstanding anti-wear properties
- Superior oxidation stability
- Water separation characteristics
- Non-corrosiveness to metals



2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com

Wocospin 3, 10 and 22

Pneumatic Tool & Spindle Lubricants



TECHNICALLY SPEAKING:

Test	Wocospin 3	Wocospin 10	Wocospin 22
Viscosity: cSt @ 40°C	3	10	22
Viscosity Index	NA	90	90
Flash Point, COC °C	112	165	182
Flash Point, COC °F	234	330	360
Pour Point °C	-22	-17	-17
Pour Point °F	-9	0	0
Cu Corrosion	1B	1B	1B
Rust, Distilled Water	Pass	Pass	Pass
Density, lbs./US Gallon	6.809	6.934	7.093
Specific Gravity	0.816	0.831	0.850

These are typical figures and do not constitute a specification.

Handling & Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet obtainable from Commonwealth Oil Corporation.



**Available in 19L/5US Gal Pails, 208L/55US Gal Drums and
1250L/330US Gal Bulk Containers**

2080 FERRISS ROAD NORTH, HARROW, ONTARIO, CANADA N0R 1G0

519-738-3503 • 800-265-3689 • FAX- 519-738-3335 inquiries@commonwealthoil.com • www.commonwealthoil.com